

PureWaterCooler™

by VERTEX

Low Cost Hot & Cold water Dispenser

Economic hot & cold water cooler with filtration makes great tasting water from your tap. Eliminates the hassle of 5-gallon bottles. Great for offices and factories.

Features

- Two temperature system
Cold: 37-50° F, Adjustable • Hot: 180° F, Autocontrol
LED indicator for hot or cold water on the front panel
- Individual on/off control switches for cold or hot water on rear panel
- Completely sealed stainless steel cold reservoir and hot tank
- Convenient, enclosed, no-drip dispensing faucets
- Safety lock for hot water faucet
- Built-in filtration system is easily accessed for replacement
Available with Reverse Osmosis filtration system
Or Standard Dual-Cartridge filtration system
- Available with ultraviolet or ozone sterilizer

Filter assembly is front door accessible (right).

Executive Gray cabinet available (far right).



ORDERING

2-Temp Model - 50 GPD Reverse Osmosis	PWC-1000R
2-Temp Model - Standard Filtration	PWC-1000F
Executive Gray Cabinet	add /EG
2-temp Model with UV sterilizer	add /UV
2-temp Model with Ozone sanitizer	add /OZ
2-temp Model w/ ProTekk Leak Detector	add /ldm
Optional stand, adds 6 inches to height	call factory
Cup holder	call factory
Replacement Filters	
Sediment	IFA-4035
GAC Carbon	IFA-4034
RO membrane, 50 GPD	MA-4203

Specifications

Weight: 58 lb.
Dimension: 13"W x 15"D x 38"H
Floor to spigot: 28"
Spigot to Drip Tray: 7.5"
Cold tank volume 1 gal
Hot tank volume .5 gal
Heating Rate: 1.5 gal/hr 180 °F
Cooling Rate: 1.5 gal/hr 37-50 °F
Voltage: 115 VAC
Power Required: 600w max
Meets Energy Star Requirements



Filter System

Standard Filter **1000F**
Stage 1: 5 micron Sediment
Stage 2: 10 micron Activated Carbon
Reverse Osmosis Filter **1000R**
Above 2 stages plus
Stage 3: 50-GPD RO Membrane
Automatic tank full control
Fully assembled
- connection hardware included
Meets Energy Star Requirements
ADA compliant

Authorized Dealer

